

AK Glass

Product Code: 7577MY-P11SM

Product Series: Coated Glass Fabric



Technical Data Sheet

PRODUCT APPLICATION

PTFE Coated Glass Fabric application is used for filtration system that works at high temperature and has ability to retain the powder of dust.

PRODUCT CHARACTERISTICS

- High temperature resistance
- Excellent chemical resistance
- Dimensional stability
- Excellent filtration efficiency

PHYSICAL PROPERTIES

Coating Agent	PTFE
Weight	800 g/m ²
Weave Style	Double Twill
Thickness	0.90 mm
Loss on Ignition	≥ 10 %
Air Permeability	4 - 8 CFM
Bursting Strength	≥ 56 Kg _f /CFM
Working Temperature	≤ 260 ° C
Color	Brown

DIMENSION

Roll Width	1650 mm
Roll Length	300 m

Safety

Obtain, read, and understand the Material Safety Data Sheet (SDS) before use of AK Glass and AK Carbon Products

FOR FURTHER INFORMATION, PLEASE CONTACT US



ASIA KANGNAM COMPANY LIMITED

69/1 Moo 6, Tambol Thakam, Amphur Bangpakong, Chachoengsao, 24130 Thailand

Phone: (+66) 38 573 635

Fax: (+66) 38 573 636, (+66) 38 573 734

This information and data contained herein is offered solely as a guide in the selection of a reinforcement material. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. The values listed for weight, thickness, and breaking strength are greige values, unless otherwise noted. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose.